
NANOH2O

The World's Only RO Membrane with Breakthrough TFN Technology

Product Data Sheet



# BW 440 R Dura

Highly durable brackish water RO membrane with superior salt rejection

## Key Features

- Enhanced chemical durability for wide cleaning pH range (1–13)
- Superior salt rejection

## Main Benefits

- High permeate water quality
- Effective cleaning performance
- Stable performance recovery after cleanings

## Ideal Applications

- Industrial process water
- Municipal drinking water


## Performance Specifications

| Item | Unit | Test Condition A | Test Condition B |
|---|---|---|---|
| Permeate Flow Rate | GPD ($m^3$/d) | 12,100 (45.8) | 12,650 (47.9) |
| Stabilized Salt Rejection | % | 99.7 | 99.74 |
| Minimum Salt Rejection | % | 99.6 | 99.65 |
| Active Membrane Area | $ft^2$ ($m^2$) | 440 (41) | |
| Feed Spacer Thickness | mil | 28 | |

The specifications outlined above are normalized performances based on the following test conditions:

- **Test Condition A**: 2,000 ppm NaCl, 225 psi (15.5 bar), 25°C (77°F), pH 7, Recovery 15%
- **Test Condition B (referential only)**: 1,500 ppm NaCl, 225 psi (15.5 bar), 25°C (77°F), pH 7, Recovery 15%
- Permeate flow rates for individual elements may vary by +20/-15%

## Dimensions and Weight




| Dimensions: mm (in) | | | Wet Weight: kg (lbs) |
|---|---|---|---|
| A | B | C | 16 (35) |
| Element Length | Element O.D. | Core Tube I.D. | |
| 1,016 (40) | 200 (7.9) | 28.6 (1.125) | |

All dimensional information is indicative and for reference only. Please contact NanoH2O for detailed technical specifications.

## Operating Specifications

| Specification | Unit | Value |
|---|---|---|
| Maximum Applied Pressure | psi (bar) | 600 (41.3) |
| Maximum Chlorine Concentration | ppm | < 0.1 |
| Maximum Operating Temperature | °C (°F) | 45 (113) |
| pH Range, Continuous Operation | | 2–11 |
| pH Range, Cleaning | | 1–13 |
| Maximum Feed Water Turbidity | NTU | 1.0 |
| Maximum Feed Water $SDI_{15}$ | | 5.0 |
| Maximum Feed Flow | gpm ($m^3$/h) | 75 (17) |
| Maximum Pressure Drop (ΔP) for Each Element | psi (bar) | 15 (1.0) |

These operating specifications are for general use. For specific applications, operation at more conservative values may ensure better performance and extended membrane life. See NanoH2O Technical Bulletins for more details.

Homepage | LinkedIn | Youtube

This product is certified to NSF/ANSI/CAN Standard 61 for drinking water systems

D-BW440RDURA-EN-093026

The product performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry-accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at www.nanoh2owater.com
The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. NanoH2O assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. All rights reserved. © NanoH2O Co., Ltd.

Please visit our website for regional contact information
www.nanoh2owater.com